




BR-134 Island Punch




BR-700 White




BR-01 Vellum



BR-357 Stone



BR-227 Wheat




BR-212 Manilla



BR-553 Dove Grey



BR-175 French Vanilla



BR-176 Snow White



BR-710 Silk



BR-05 Doe



BR-166 Cashew



BR-555 Silver Pearl



BR-267 Ochre




BR-220 Aria



BR-135 Slate




BR-163 Terracotta



BR-329 Buff



BR-130 Pewter



BR-214 Milkweed



BR-709 Rice



BR-177 Dune



BR-492 Papyrus



BR-164 French Blue



BR-131 Sky



BR-723 Regatta



BR-222 Marine



BR-563 Diplomat Blue



BR-47 Nickel



BR-162 Cinnamon



BR-24 Jacobean



BR-136 Forest Green



BR-381 Shadow



BR-134 Island Punch



BR-178 Sable



BR-165 Artichoke



BR-25 Chestnut



BR-719 Charcoal



BR-167 Cypress



BR-705 Red



BR-133 Purple



BR-703 Pecan



BR-132 Burgundy



BR-45 Sedona



BR-30 Ravenwing

GENERAL SPECIFICATIONS

- Composition: 100% Polyurethane Surface, 100% Reinforced Rayon backing
- Weight: Approx. 9.7 oz. Per Square yd
- Thickness: Approx. 0.95 Millimeters
- Width: 54 inches



Luxor Leather™
FEEL THE DIFFERENCE

PERFORMANCE

- Abrasion: ASTM D4157 / 400,000 Double Rubs (Wyzenbeek)
- Hydrolysis: 16+ weeks ASTM D3690 sec.611 (Hydrolytic Stability)
- Adhesion of coating: 16+ weeks ASTM D2261
- Tear Strength: ASTM D751
- Breaking Strength: ASTM D751
- Tensile Strength: BS EN ISO 1421

COLORFASTNESS

- 1,000 Hours AATCC-16A, Carbon / Arc Outdoor

FLAMMABILITY REQUIREMENTS

- ASTM E84 (Adhered- Class A)
- CA TB 117-2013 Pass
- FMVSS 302 & 95/28 Annex IV-pass
- NFPA 260 - Class 1
- UFAC-Class 1
- CA AB 2998

Note: These fabrics can be treated to pass FAR 25.853 12 second Vertical

For more information about cleaning and care instructions, please feel free to give us a call.